

UNIFIX 20S

For Unisun 10.12M/ 10.24M/ 20.12M/ 20.24M Landscape orientation Masthead or middle of the mast Mounting flanges in option Ref 0286



UNIFIX 100S

For Unisun 80.12M/ 100.12M/ 100.24M/ 120.12BC Landscape or portrait orientation Masthead or middle of the mast Mounting flanges in option Ref 0323



UNIFIX 200S
For Unisun 200.24M
Landscape or portrait orientation
Masthead or middle of the mast
Mounting flanges in option
Ref 0941



UNIFIX 50S

For Unisun 30.12M/ 50.12M/ 50.24M/ 55.12BC Landscape orientation Masthead or middle of the mast Mounting flanges in option Ref 0293



UNIFIX 150S

For Unisun 150.12M/ 150.24M/ 150.12BC/ 200.12BC Landscape or portrait orientation Masthead or middle of the mast Mounting flanges in option Ref 0866



For Unisun 300.12M
Landscape or portrait orientation
Masthead or middle of the mast
Mounting flanges in option
Ref 2082

<u>†</u>

Mounting Brackets - Reclinable UNIFIX S

POLE & MAST

RECLINABLE BRACKETS FOR UNIVERSAL PANELS

Thanks to their universal fastening system, UNIFIX S mounting bracket adapts to all signal masts.

Simply, slide your flanges with the M8 or M10 screws onto the rear rail and then tighten.

UNIFIX S offers the possibility to choose the inclination. The tilting system enables you to optimize the electrical production according to the area and the period of use.

With its Easy Install system and their light aluminium structure, its mounting can easily be done alone, without extra assistance.





OPTION UNIFIX S or SF POST FLANGES STAINLESS STEEL FASTENERS (x2)

Diam 40-60 mm Ref 2631

Diam 60-90 mm Ref 2648

Diam 90-130 mm Ref 2655

Diam 130-190 mm Ref 2662

UNITECK



Adaptable on all signal

G



Corrosion resistant aluminium + A4 stainless steel screws



Easy to install



Reclinable from 30 to 60°



Can be fixed on any support



With flanges or U clamps (flanges and M8 or M10 screws in option)



Designed, made in France





system to optimize your electrical performances

Easy installation system Its upper cap relieves



the weight of the installation so that their mounting can easily be done alone, without extra assistance. This cap can be removed afterwards for a fixation on the middle of the mast. It is used on pole with a maximum of 130mm diameter.
For UNIFIX 100S /150S /200S.

